



MESA Specialty Gases & Equipment
3619 Pendleton Avenue, Suite C
Santa Ana, California 92704 USA

MATERIAL SAFETY DATA SHEET

Chemical Name: 2 Component Sulfur Gas in n-Butane w/ Helium Pad
Chemical Formula: COS,CH ₃ SCH ₃ /n-C ₄ H ₁₀
Chemical Family: Flammable Liquid Mixture
Hazard Classification: Liquefied Gas, Flammable, N.O.S., Flammable Gas, UN3161, Red Label
Phone Number for Information: Infotrac
Emergency Contact: 800-535-5053 (Int'l 352-323-3500)

SECTION 1 – MATERIAL IDENTIFICATION

COMPONENT	CAS No.	CONCENTRATION	OSHA PEL	ACGIH TLV
Dimethyl Sulfide	74-93-1	0.1-1000 ppm	Not Established	Not Established
Carbonyl Sulfide	463-58-1	0.1-1000 ppm	5 ppm	1070 ppm
n-Butane	106-97-8	Balance	Not Established	800 ppm
Helium	7440-59-7	Pressure Pad	None	None

SECTION 2 – PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A	Specific Gravity (H₂O)= 0.7, 20 deg C): N/A
Vapor Pressure (psia, 20 deg C): 31	Melting Point: N/A
Vapor Density (Air = 1): 2.11	Evaporation Rate (Butyl Acetate = 1): N/A
Solubility in Water: N/A	
Appearance and Odor: Colorless, Pungent, sweet odor of rotten eggs	

SECTION 3 – FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/A – flammable gas	Flammable Limits: LEL: 1.8% UEL: 8.4%
Extinguishing Media: Use appropriate media for surrounding fire such as CO ₂ foam extinguishers	
Special Fire Fighting Procedures: Wear NIOSH/MSHA approved SCBA and full protective equipment. Stop flow of gas if this can be done safely. Use water spray to keep cylinders cool.	
Unusual Fire and Explosion Hazards: Gas cylinders may rupture violently when exposed to fire. Cylinder valve is equipped with a pressure relief device to safely vent the cylinder if it is exposed to elevated pressure in a fire.	

DISCLAIMER

Information contained in this data sheet is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable. But the accuracy and completeness thereof, is not guaranteed and no warranty of any kind, either expressed or implied, is made with respect thereto. Since MESA Specialty Gases and Equipment Division of MESA International Technologies, Inc. shall have no control over the use of the product described herein, we assume no liability for loss or damage incurred from the proper or improper use of such product.



SECTION 4 – REACTIVITY HAZARD DATA		
Stability: Flammable Gas		
Incompatibility: Oxidizing materials		
Hazardous Decomposition or Byproducts: None		
Hazardous Polymerization: None		

SECTION 5 – HEALTH HAZARD DATA		
Routes of Entry: Inhalation		
Health Hazards (Acute and Chronic): Mixture is a simple asphyxiant which will displace oxygen in air necessary for life. Sulfur gases in high concentrations may be fatal.		
Carcinogenicity: NTP? No	IARC Monographs? No	OSHA Regulated? No
Medical Conditions Generally Aggravated by Exposure:		
Emergency and First Aid Procedures: Remove person to uncontaminated area. SCBA may be required to prevent asphyxiation of rescue workers. Keep warm and at rest. Lay victim face down with head and chest lower than hips to improve drainage from lungs. If breathing is labored, administer pure oxygen. If breathing has stopped, start artificial respiration. Get immediate medical attention for serious exposure.		

SECTION 6 – PRECAUTIONS FOR SAFE HANDLING AND USE		
Steps to be Taken in Case Material is Released or Spilled: Ventilate enclosed areas. Move leaking cylinder to fume hood or safe outdoor area.		
Precautions to be Taken in Handling or Storing: Gas or liquefied gas are to be used with the appropriate pressure regulating control and high pressure equipment. Cylinders should be secured with mounting brackets away from heavily traveled areas. Keep cylinder in dry, cool, well ventilated area away from heat, flame, sparks or corrosive chemicals. Cylinders should be moved by suitable hand trucks.		
Other Precautions: Use monitoring equipment if hazardous conditions are suspected or likely to occur.		

SECTION 7 – CONTROL MEASURES		
Respiratory Protection (Specify Type): Use self-contained breathing apparatus in emergency or rescue situations.		
Ventilation: Enclosed area must be provided with general or local exhaust ventilation to avoid hazardous conditions.		
Protective Clothing or Equipment: Safety glasses and shoes should be worn when handling high pressure cylinders or hazardous materials.		